

PRODUCT DATA SHEET

CAP197 MULTI-PURPOSE WATER BASED PRIMER

PRODUCT	CAP197 multi-purpose water based etch primer
DESCRIPTION/USES	CAP197 is a fast drying, water based, multi-purpose primer specifically designed for use in conjunction with CAP Fire Resistant Finishes. It has been formulated with an acrylic resin to provide excellent adhesion over a variety of interior surfaces like plasterboard high gloss coatings, plastic, glass, ceramic tiles, glazed block and other high density materials.
SURFACE PREPARATION	Standard painting practices and procedures which are followed normally in the painting profession should be used to clean and prepare surfaces before painting. NOTE: For use on wood, check a small section before proceeding. Application may show grain raising.

APPLICATION INFORMATION

METHOD	Spray preferred. Brush or roll small areas only.
DRYING TIME	30 minutes to touch; 30-45 minutes to recoat at 21°C and 50% RH. Topcoat within 48 hours.
THINNING	Not required. Reduce with water, if necessary. Over-thinning may result in loss of hide and retard drying.
TINTING	Not recommended
CLEAN UP	Warm soapy water while coating is wet. After drying, use lacquer thinner. CAUTION: Do not allow to dry in equipment.
HMIS	Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: H.
ENVIRONMENTAL	Consult with local regulatory and governmental agencies for VOC compliance and methods of disposal.

SPECIFICATIONS

COLOUR	White
SOLIDS BY VOLUME	49%
WEIGHT PER LITRE	1.32 kg
GLOSS	Flat (@ 60° angle)
COVERAGE	Depends on surface porosity, texture and method of application.
SHELF LIFE	One year
MAXIMUM VOCs	200 grams/litre
CAUTION	Protect from freezing. Do not apply when temperature of paint or surface is below 18°C or above 25°C or relative humidity is above 75%.