

PRODUCT DATA SHEET

CAP827 CLEAR TOP COAT

PRODUCT	CAP827M or CAP827S low sheen acrylic clear coating
DESCRIPTION/USES	CAP827M or CAP827S is a low VOC, water based clear coating for use exclusively as a protective top coat for CAP800 on wood.
SURFACE PREPARATION	All surfaces should be clean, dry (below 15% moisture), and free of dust, grease or other contaminants.

APPLICATION INFORMATION

MATERIAL PREPARATION	Mix thoroughly before application.
METHOD	Airless spray
DRYING TIME	Dry to Touch: 1/2 hour at 24°C and 50% relative humidity (RH) Re-coat: 2 to 4 hours at 24°C and 50% relative humidity (RH) Full Cure: 20 days
THINNING	Do NOT thin
CLEAN UP	Water
HMIS	Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: E.
ENVIRONMENTAL	Consult with local regulatory and governmental agencies for methods of disposal.

SPECIFICATIONS

COLOUR	Clear
SOLIDS BY VOLUME	33%
WEIGHT PER LITRE	1.12 kg
GLOSS	Low sheen
COVERAGE	10m ² /litre on smooth sealed surfaces per coat
SHELF LIFE	One year
MAXIMUM VOCs	20 grams/litre
CAUTION	Protect from freezing. Do not apply when temperature of paint or surface is below 18°C or above 25°C or relative humidity is above 75%.